



A Skellerup Industries Company



Retrofit[®] Original

When it has to flash
around, not over







FS 520679
IN QUALITY ISO 9001



- Fast and Efficient installation**
Wraps around existing or difficult to access pipes
- Snaps together in seconds**
The built-in crimp means no loose clips or rivets
- Grips tight and stays tight**
Made from DEKS quality polymer compound
- Our base makes easy work**
Aluminium base conforms to roof with ease
- Twenty year warranty**
Just fit it and forget it - we've got you covered

www.deks.com.au

Selection Guide

| Code | Pipe Size mm | Pipe Size inches | Roof Pitch | Base mm | Colours |
|--------|--------------|------------------|----------------|-------------|---|
| RF 801 | 20-70mm | ¾ - 2 ¾" | 0-40° or 10/12 | 160mm |  |
| RF 802 | 50-190mm | 2 - 7 ½" | 0-40° or 10/12 | 273mm |  |
| RF 803 | 85-255mm | 3 ¼ - 10" | 0-40° or 10/12 | 369mm |  |
| RFS 4 | 235-425mm | 9 ¼ - 16 ¾" | 0-40° or 10/12 | 762 x 680mm |  |


Red Silicone
Grey (EPDM)
Black (EPDM)


Available in Black and Grey EPDM or Red Silicone


EPDM will withstand constant temperatures at the roofline of -50°C (-58°F) to 115°C (239°F) and up to 150°C (302°F) intermittently
Red Silicone will withstand constant temperatures at the roofline of -50°C (-58°F) to 200°C (392°F) and up to 250°C (482°F) intermittently


Please Note That the outside temperature of the pipe may be significantly different to the exit temperature of the appliance.


Installation Information


- 

Trim cone to suit pipe size using sharp tin snips.
- 

With clip in downstream position, wrap top of cone around pipe and engage metal teeth in opposing pockets starting at the top.
- 

To assist locating clip into pocket, place hand behind seam. Fasten clip with pliers or multitools, working from top to base. Do not over crimp.
- 

Apply sealant to underside of Dektite base and shape to roof by hand.
- 

Fasten flashing down and secure clip by placing a fastener either side of clip first.
- 

Apply sealant to top of crimp closure and any other potential leak areas.



- Always use the neutral cure low modulus silicone for sealing
- In corrosive and coastal environments fix using blind aluminium rivets

Need to flash a square penetration? Contact DEKS to discuss the square flashing range.